# **KLASIK B**





Refrigerated display cabinet with suspended aggregate, which can perfectly meet the requirements for food storage, but also complement the design of the establishment with its classic shape, so it can be placed in all interiors of catering establishments. A sophisticated cooling system with automatic defrosting keeps all presented food fresh and dry for a long time.

#### **DOUBLE GLAZING**

reduce energy consumption, reduce condensate formation, which contributes to better visibility of presented products

#### USE OF ENVIRONMENTALLY FRIENDLY REFRIGERANTS

higher energy efficiency of cooling systems significantly reduces the environmental burden

#### LED LIGHTING

ensures visibility of the products on display

EASY ACCESS TO THE DISPLAY CASE trouble-free maintenance and easy operation

SPECIAL DESIGN OF THE BAKER creates a stable environment and significantly extends the shelf life of stored food

## **Designed for:**

- cafés
- patisseries
- bakeries
- food outlets
- delicatessen
- grocery stores
- fast food restaurants
- bistros, corporate, school or hospital canteens
- restaurants
- and more





Self-service variant, customer's view

Service variant, operator's view

# **KLASIK B**



DRINKS

300 W/230 V



PACKAGED FOOD

KL120765FB2G10

UNPACKAGED FOOD BAGUETTE

SANDWICHES



1200 × 500/700 × 650



Code	Number of shelves	Type of sale	Number of doors	Position of the unit from the operator's point of view	W × D × H (mm)	Power/voltage
KL080765FB	2	Service	_	Right	800×500/700×650	200 W/230 V
KL100765FB	2	Service	_	Right	1000×500/700×650	210 W/230 V
KL120765FB	2	Service	_	Right	1200 × 500/700 × 650	300 W/230 V
KL080765FB2F10	2	Self-service	2×3	Right	800×500/700×650	200 W/230 V
KL100765FB2G10	2	Self-service	3×3	Right	1000 × 500/700 × 650	210 W/230 V

Other dimensions and variants not listed here are available on request from your sales representative.

3×3

Self-service

### Accessories

2

_	Code	Name	Shelf dimensions in mm	
7	KL080000FA01	upper shelf width 800 mm including stainless steel side brackets	350 x 722	
_	KL100000FA01	top shelf width 1000 mm including side stainless steel brackets	350 x 922	
Ĺ	KL120000FA01	top shelf width 1200 mm including side stainless steel brackets	350 x 1122	
	KL080000FA02	lower shelf width 800 mm including side stainless steel brackets	350 x 722	
	KL100000FA02	bottom shelf width 1000 mm including side stainless steel bracket	350 x 922	
7	KL120000FA02	bottom shelf width 1200 mm including side stainless steel brackets	350 x 1122	
	$\vee$ $\vee$ $\vee$			

Right

### Technical description

- all stainless steel construction
- sliding glass door with stainless steel continuous handles and double insulated glass in the self-service version, the hinged door is on the customer's side
- LED lighting, located in the front pillars, provides ideal lighting for the entire space
- bottom stainless steel bottom: can be used as additional space for product presentation
- static cooling
- user adjustable shelf height
- R290 refrigerant

## Standard equipment

- digital thermostat with temperature control from +4 °C
- automatic defrost
- digital temperature display
- ON/OFF switch
- LED lighting
- tempered glass shelves 6-8 mm thick with polished edges
- double wall glass for excellent insulation properties

tel.: +420602386569 e-mail: sales@conteg-gastro.cz www.conteg-gastro.cz/en