KLASIK S





FOOD

UNPACKAGED Food BAGUETTE SANDWICHES

BAKERY PRODUCTS

19

Refrigerated display cabinet with an aggregate located in the right or left part of the display cabinet, which allows full use of the interior of the display cabinet. It is a type of smaller table-top display cabinet designed for direct placement on the counter, which is easy to move and therefore also suitable for stall sales, e.g. at markets or festivals.

DOUBLE GLAZING

reduce energy consumption, reduce condensate formation, which contributes to better visibility of presented products

USE OF ENVIRONMENTALLY FRIENDLY REFRIGERANTS

higher energy efficiency of cooling systems significantly reduces the environmental burden

LED LIGHTING

ensures visibility of the products on display

EASY ACCESS TO THE DISPLAY CASE

trouble-free maintenance and easy operation

POSSIBILITY OF OWN CHOICE OF AGGREGATE LOCATION - right/left

SPECIAL DESIGN OF THE BAKER creates a stable environment and significantly extends the shelf life of stored food

Designed for:

- cafés
- patisseries
- bakeries
- food outlets
- delicatessen
- grocery stores
- fast food restaurants
- bistros, corporate, school or hospital canteens
- restaurants
- and more





Service variant, operator's view



KLASIK S



210 W/230 V

| | | | | | Ê | Ð | Å |
|------------------------|------------------|----------------------|----------------------------|--------------------|--|----------------------|---------------|
| | PACKAGED Food | | UNPACKAGED Food | | BAGUETTE SANDWICHES | BAKERY PRODUCTS | DRINKS |
| $\overline{\lambda}$ | | \prec / | \times \land \rangle | | \rightarrow | | |
| Y | Code | Number of shelves | Type of sale | Number of doors | Position of the unit from the operator's point of view | W × D × H (mm) | Power/voltage |
| | KL100765FR | 2 | Service | _ | Right | 1000 × 500/700 × 650 | 200 W/230 V |
| $\left \right\rangle$ | KL120765FR | 2 | Service | _ | Right | 1200 × 500/700 × 650 | 210 W/230 V |
| | KL100765FL | 2 | Service | _ | Left | 1000 × 500/700 × 650 | 200 W/230 V |
| Y | KL120765FL | 2 | Service | - | Left | 1200 × 500/700 × 650 | 210 W/230 V |
| | KL100765FR2F10 | 2 | Self-service | 2×3 | Right | 1000 × 500/700 × 650 | 200 W/230 V |
| | KL120765FR2G10 | 2 | Self-service | 3 × 3 | Right | 1200 × 500/700 × 650 | 210 W/230 V |
| | KL100765FL2F10 | 2 | Self-service | 2×3 | Left | 1000 × 500/700 × 650 | 200 W/230 V |

Other dimensions and variants not listed here are available on request from your sales representative

Self-service

3 x .3

Accessories

2

KI 120765EL 2G10

| | Code | Name | Shelf dimensions in mm | |
|----|--------------|--|------------------------|----|
| | KL080000FA01 | upper shelf width 800 mm including stainless steel side brackets | 300 x 722 | _/ |
| | KL100000FA01 | top shelf width 1000 mm including side stainless steel brackets | 300 x 922 | |
| | KL080000FA02 | lower shelf width 800 mm including side stainless steel brackets | 300 x 722 | _7 |
| ζ. | KL100000FA02 | bottom shelf width 1000 mm including side stainless steel brackets | 300 × 922 | |
| | | | | |

Left

Technical description

- all stainless steel construction
- sliding glass door with stainless steel continuous handles and double insulated glass in the self-service version, the hinged door is on the customer's side
- LED lighting, located in the front pillars, provides ideal lighting for the entire space
- bottom stainless steel bottom: can be used as additional space for product presentation
- static cooling
- user adjustable shelf height
- R290 refrigerant

Standard equipment

1200 × 500/700 × 650

- digital thermostat with temperature control from +4 °C
- automatic defrost
- digital temperature display
- ON/OFF switch
- LED lighting
- tempered glass shelves 6-8 mm thick with polished edges
- double wall glass for excellent insulation properties

tel.: +420 602 386 569 e-mail: sales@conteg-gastro.cz www.conteg-gastro.cz/en