

# GENERUS T

CONTEG  
GASTRO



MEAT



SMOKED  
MEAT



CHEESE



DRINKS



**Glass door refrigerated display cabinet with aggregate located in the upper part. It is a display cabinet with a variable system of shelves, hooks, bars and special holders. It is designed for presentation and storage of meat, sausages or cheese, or beverages.**

**INSULATING DOUBLE GLAZING OF SLIDING DOORS** reduce energy consumption, reduce condensate formation, which contributes to for better product visibility

**SOPHISTICATED COOLING SYSTEM** with automatic defrosting keeps all presented products fresh for a long time and significantly extends their shelf life

**LED LIGHTING OF INDIVIDUAL SHELVES** ensures visibility of the products on display

**EASY ACCESS TO THE DISPLAY ASE** trouble-free maintenance and easy operation

**THE HOOD WITH DEFROSTING RODS** located at the top of the display case ensures the ideal temperature for keeping fresh meat on special hooks

**OPTIONAL AFFILIATION**

## Designed for:

- mainly for meat and butcher shops, where the display case is installed directly on the wall or placed on a counter against the wall behind the operator's back
- other catering** establishments where chilled products need to be preserved and made visible



# GENERUS T

**CONTEG**  
GASTRO



MEAT



SMOKED  
MEAT



CHEESE



DRINKS

Code	Type of sale	Version	Doors	Location of the aggregate	W × D × H (mm)	Power/voltage
GE104516FT	Service	Glass door	sliding	above	1000 × 450 × 1550	860 W/230 V
GE124516FT	Service	Glass door	sliding	above	1200 × 450 × 1550	1060 W/230 V
GE154516FT	Service	Glass door	sliding	above	1500 × 450 × 1550	1320 W/230 V
GE204513FS	Service	Glass door	sliding	above	2000 × 450 × 1550	1970 W/230 V

## Technical description

- all stainless steel construction
- control and positioning of the unit at the top
- sliding glass door with stainless steel continuous handles with double insulating glass
- static cooling
- optional accessories
- user adjustable accessory height
- condensate drain in the bottom of the display case, standard approx. 160 mm from the right edge, 40 mm from the back of the display case
- R407H refrigerant

## Standard equipment

- digital thermostat with temperature control from +2°C
- automatic defrost
- digital temperature display
- ON/OFF switch
- LED lighting with adjustable colour spectrum
- double insulating glass of sliding doors

tel.: +420 602 386 569  
e-mail: sales@conteg-gastro.cz  
www.conteg-gastro.cz/en