MODUS B





Refrigerated display cabinet with suspended aggregate is designed to be built into the counter. It combines a modern look with a long tradition. Its innovative design makes it suitable for all interiors of catering establishments. Both the interior of the display case and the upper stainless steel surface can be fully used for the presentation of the displayed products. The displayed goods are spectacularly illuminated by pleasant LED lighting.

DOUBLE GLAZING

reduce energy consumption, reduce condensate formation, which contributes to better visibility of presented products

USE OF ENVIRONMENTALLY FRIENDLY REFRIGERANTS

higher energy efficiency of cooling systems significantly reduces the environmental burden

LED LIGHTING

ensures visibility of the products on display

EASY ACCESS TO THE DISPLAY CASE trouble-free maintenance and easy operation

SPECIAL DESIGN OF THE BAKER creates a stable environment and significantly extends the shelf life of stored food

Designed for:

- cafés
- patisseries
- bakeries
- food outlets
- delicatessen
- grocery stores
- fast food restaurants
- bistros, corporate, school or hospital canteens
- restaurants
- and more





Service variant, operator's view

Self-service variant, customer's view

MODUS B



DRINKS



PACKAGED FOOD

UNPACKED FOOD

BAGUETTE SANDWICHES



PRODUCTS

	Code	Number of shelves	Type of sale	Number of doors	Position of the unit from the operator's point of view	W × D × H (mm)	Power/voltage
_	M0080565FB	2	Service	-	Right	800 × 500 × 650	200 W/230 V
	M0100565FB	2	Service	-	Right	1000 × 500 × 650	210 W/230 V
/	M0120565FB	2	Service	_	Right	1200 × 500 × 650	300 W/230 V
	M0080565FB2F10	2	Self-service	2×3	Right	800 × 500 × 650	200 W/230 V
_	M0100565FB2G10	2	Self-service	3 × 3	Right	1000 × 500 × 650	210 W/230 V
_	M0120565FB2G10	2	Self-service	3×3	Right	1200 × 500 × 650	300 W/230 V

Other dimensions and variants not listed here are available on request from your sales representative.

Accessories

Code	Name	Shelf dimension in mm
M0080500FA01	shelf width 800 mm including stainless steel side brackets	300 x 722
M0100500FA01	shelf width 1000 mm including stainless steel side brackets	300 x 922
M0120500FA01	shelf width 1200 mm including stainless steel side brackets	300 x 1122

Technical description

- all stainless steel construction
- sliding glass door with stainless steel continuous handles and double insulated glass
- in the self-service version, the hinged door is on the customer's side
- LED lighting, vertically positioned in the front columns, provides ideal illumination of the entire space
- bottom stainless steel bottom: can be used as additional space for product presentation
- static cooling
- user adjustable shelf height
- R290 refrigerant

Standard equipment

- digital thermostat with temperature control from +4 °C
- automatic defrost
- digital temperature display
- ON/OFF switch
- LED lighting
- tempered glass shelves 6-8 mm thick with polished edges
- double wall glass for excellent insulation properties

tel.: +420602386569 e-mail: sales@conteg-gastro.cz www.conteg-gastro.cz/en