MODUS T





Refrigerated display cabinet with aggregate located in the upper part of the display cabinet. It is a type designed for direct placement on the counter. Both the interior of the display case and the upper stainless steel surface can be fully used for the presentation of the displayed products. The display case is easy to move and therefore also suitable for stall sales, e.g. at markets or festivals.

DOUBLE GLAZING

reduce energy consumption, reduce condensate formation, which contributes to better visibility of presented products

USE OF ENVIRONMENTALLY FRIENDLY REFRIGERANTS

higher energy efficiency of cooling systems significantly reduces the environmental burden

LED LIGHTING

ensures visibility of the products on display

EASY ACCESS TO THE DISPLAY CASE trouble-free maintenance and easy operation

SPECIAL DESIGN OF THE BAKER creates a stable environment and significantly extends the shelf life of stored food

Designed for:

- cafés
- patisseries
- bakeries
- food outlets
- delicatessen
- grocery stores
- fast food restaurants
- bistros, corporate, school or hospital canteens
- restaurants
- and more





Service variant, operator's view

Self-service variant, customer's view

MODUS T



DRINKS



PACKAGED FOOD UNPACKED FOOD

BAGUETTE SANDWICHES



| 4 | Code | Number of shelves | Type of sale | Number of doors | Position of the unit from the operator's point of view | W×D×H (mm) | Power/voltage |
|----------|----------------|----------------------|--------------|--------------------|--|------------------|---------------|
| | M0080585FT | 2 | Service | _ | above | 800 × 500 × 850 | 200 W/230 V |
| | M0100585FT | 2 | Service | - | above | 1000 × 500 × 850 | 210 W/230 V |
| / | M0120585FT | 2 | Service | - | above | 1200 × 500 × 850 | 300 W/230 V |
| <u>_</u> | M0080585FT2F10 | 2 | Self-service | 2×3 | above | 800 × 500 × 850 | 200 W/230 V |
| | M0100585FT2G10 | 2 | Self-service | 3 × 3 | above | 1000 × 500 × 850 | 210 W/230 V |
| ۲. | M0120585FT2G10 | 2 | Self-service | 3×3 | above | 1200 × 500 × 850 | 300 W/230 V |

Other dimensions and variants not listed here are available on request from your sales representative.

Accessories

| Code | Name | Shelf dimensions in mm |
|--------------|---|------------------------|
| M0080500FA01 | shelf width 800 mm including stainless steel side brackets | 300 x 722 |
| M0100500FA01 | shelf width 1000 mm including stainless steel side brackets | 300 x 922 |
| M0120500FA01 | shelf width 1200 mm including stainless steel side brackets | 300 x 1122 |

Technical description

- all stainless steel construction
- sliding glass door with stainless steel continuous handles and double insulated glass in the self-service version, the hinged door is on the customer's side
- LED lighting, vertically positioned in the front columns, provides ideal illumination of the entire space
- bottom stainless steel bottom: can be used as additional space for product presentation
- dynamic cooling
- user adjustable shelf height
- R290 refrigerant

Standard equipment

- digital thermostat with temperature control from +4 °C
- automatic defrost
- digital temperature display
- ON/OFF switch
- LED lighting
- tempered glass shelves 6-8 mm thick with polished edges
- double wall glass for excellent insulation properties

tel.: +420 602 386 569 e-mail: sales@conteg-gastro.cz www.conteg-gastro.cz/en